







# **Benefits:**

- Access hard to reach instrumentation from the ground or your truck
- Improve plant personnel safety
- Easy instrument configuration using PC's or Mobile's without bulky modules or wires
- Less clutter on desk or workbench

## Features:

- Bluetooth v2.0
- Reliable wireless communication up to 275 ft (83.8m)
- Internal antenna
- Rechargeable Li-Ion battery via mini-USB connector
- Integral heavy duty HART Minigrabber connectors
- Meets HART Physical Layer Spec HCF\_SPEC-54
- High security 128 bit encryption
- Compact size 2.00" x 2.75" x 0.80" (50mm x 70mm x 20mm)
- Rugged ABS plastic enclosure
- HART Modem Test Program included for PC and Pocket PC
- Integrated loop for hanging strap attachment
- Each unit 100% tested
- 1 Year warranty







# **Specifications:**

## Enclosure

Material Dimensions Total Unit Weight

<u>Cables</u>

HART Cable Length HART Cable Connectors

#### HART

Interface Output Leakage Connections Specifications

## <u>Computer</u>

Operating System

### <u>Bluetooth</u>

Specifications Frequency Class 1 Master Distance Class 2 Master Distance

## <u>Battery</u>

Type Life

#### **Environmental**

Operating Temperature Storage Temperature Humidity High strength ABS Plastic 2.00" x 2.75" x 0.80" (50mm x 70mm x 20mm) 6 oz (170 g)

4' (1.2 m) Mini-Grabber

Capacitive coupling 600 mVpp < 10 uA Across loop resistor or HART field device HART 4, HART 5, HART 6, HART 7, HART Physical Layer Spec HCF\_SPEC-54

Windows NT, 2000, XP, Vista (32/64), 7 (32/64)

Bluetooth v2.0 2.4 GHz 275' (83.8m) 25' (7.6m)

Rechargeable Li-Ion 19 hours continuous use

0 degC to 50 degC (32 degF to 122 degF) -40 degC to 85 degC (-40 degF to 185 degF) 0% to 99% (non-condensing)